

HYDRAULIC BOTTLE JACKS



JET INDUSTRIAL BOTTLE JACKS

- These JET industrial hydraulic bottle jacks have earned a reputation for extra heavy duty performance, reliability and dependability for over 40 years
- Tested to over 150% of rated capacities
- Electrically welded base and cylinder assures strength and eliminates leaks
- Rigidly adheres to JIS and ANSI standards
- Available in standard and low profile models
- Not affected by temperature extremes
- All models work in upright, angle or horizontal positions
- Equipped with convenient extension screw for low pick up height adjustment
- Cleated steel lift saddle for safest operator conditions
- Fully serviceable; common release valve assemblies and other interchangeable parts allow quick repairs



PROD. NO.	MOD. NO.	Rated Cap'y (Tons)	Closed Height	Piston Height	Head Screw Height	Max. Height	Base Size	Handle Type (Piece)	Ship Wt. (lbs)
140101	JHJ-2	2	7-1/8"	4-1/2"	2"	13-9/16"	4-5/16" x 2-9/16"	2	6
140102	JHJ-3	3	7-1/2"	4-1/2"	2-3/8"	14-3/8"	4-1/2" x 2-13/16"	2	6
140103	JHJ-5	5	7-7/8"	4-3/4"	2-3/4"	15-3/8"	5-3/16" x 15/16"	3	8
140104	JHJ-8	8	7-7/8"	4-3/4"	2-3/4"	15-3/8"	6" x 3-1/2"	3	12
140105	JHJ-12-1/2	12-1/2	9-1/2"	5-7/8"	3-1/8"	18-1/2"	6-1/2" x 4-3/16"	3	18
140106	JHJ-12-1/2LP	12-1/2	6-3/4"	3-3/4"	3"	13-3/8"	6-1/2" x 4-3/16"	1	14
140107	JHJ-17-1/2	17-1/2	10-7/16"	6-1/2"	3-1/8"	20-1/16"	7-1/8" x 4-5/8"	3	23
140108	JHJ-17-1/2LP	17-1/2	6-3/4"	3-1/2"	2-3/4"	13"	7-1/8" x 4-5/8"	1	18
140109	JHJ-22-1/2	22-1/2	10-5/8"	6-1/4"	—	16-5/16"	7-3/16" x 5-1/16"	3	27
140110	JHJ-22-1/2LP	22-1/2	7-1/8"	3-3/8"	1-9/16"	12"	7-3/16" x 5-1/16"	1	22
140111	JHJ-35	35	11"	6-1/4"	—	17-5/16"	7-9/16" x 5-9/16"	1	41
140112	JHJ-60	60	12"	6-3/4"	—	18-11/16"	9-5/16" x 7-3/8"	1	82

JET HYDRAULIC TOE JACKS

- For use where exceptionally low pick up height is required
- Extra wide base for maximum stability
- 200° handle socket for operation from any direction
- Load can be applied to toe or head
- Complete with overload protection
- Electrically welded base and cylinder assures strength and eliminates leaks
- Rigidly adheres to JIS and ANSI standards
- Not affected by temperature extremes



PROD. NO.	MOD. NO.	Rated Cap'y (Toe)	Rated Cap'y (Head)	Min. Ht. (Toe)	Max. Ht. (Toe)	Min. Ht. (Head)	Max. Ht. (Head)	Base Size (LxW)	Ship Wt. (lbs)
149123	JTJ-5SV	5 ton	6 ton	1"	5-5/8"	11-1/2"	16-1/8"	10-5/8" x 7-1/8"	50
149125	JTJ-10SV	10 ton	14 ton	1-1/4"	6-3/4"	13"	18-1/2"	11-1/4" x 9-1/2"	80