

Technical Specifications – Model LV-S2

Projector Type	Multi-media projector
Dimensions (W x H x D)	10.24" x 2.00" x 9.63" (260mm x 76mm x 244.5mm)(not including adjustable feet)
Net Weight	6.39lbs (2.9kg)
LCD Panel System	0.7" TFT active matrix type, 3 panels
Panel Resolution	800 x 600 dots
Number of Pixels	1,440,000 (800 x 600 x 3 panels)
Colour System	PAL, SECAM, NTSC, NTSC4.43, PAL-M and PAL-N
High Definition TV Signal	480i, 480p, 575i, 575p, 720p, 1035i and 1080i
Scanning Frequency	H-Sync. 15 ~ 80 KHz, V-Sync. 50 ~ 100 Hz
Projection Image Size (Diagonal)	Adjustable from 29" to 200"
Horizontal Resolution	500 TV lines (S-Video)
Projection Lens	F 1.6 ~ 2.0 lens with f 20.3 mm ~ 28.2 mm with natural zoom and focus
Throw Distance	3.6' ~ 26.2' (1.1m ~ 8m)
Projection Lamp	150W
Video Input Jacks	RCA Type x 3 (Video/Y, Pb/Cb, Pr/Cr) and Mini DIN 4 pin x 1 (S-Video)
Audio Input Jacks	Mini Jack (stereo) x 1
Computer Input Terminals	(VGA) HDB 15 Terminal x 1
Computer Audio Input Jack	Mini Jack (stereo) x 1
Control Port Connector	Mini DIN 8 pin x 1
USB Connector	USB Series B receptacle x 1
Audio Output Jacks	Mini Jack (stereo) x 1
Internal Audio Amp	1.0W RMS
Built-in Speaker	1 speaker, 1.4" x 0.8" (35mm x 20mm)
Feet Adjustment	0° to 10.7°
Voltage and Power Consumption	AC 100 ~ 120V (2.5 Max. Ampere), 50 / 60 Hz
Operating Temperature	41° F ~ 95° F (5° C ~ 35° C)
Storage Temperature	14° F ~ 140° F (-10° C ~ 60° C)
Remote Control Unit	Power Source : Lithium Type (CR 2025 / 3.0V) Operating Range : 16.4' (5m)/ ± 30° Dimensions : 2.1" x 0.28" x 5.3" (54mm x 7mm x 135mm) Net Weight : 1.27oz (36g) Including Battery
Accessories	Owners Manual AC Power Cord Remote Control Unit and Battery VGA Cable Carrying Bac Lens Cover